


# 1.Features

- Ideal for retro-fit of existing T8 / T5 fixture
- PMMA light guide for reliable quality
- Flexible sizes for different projects
- Plug and play
- Up to 120lm/w energy saving
- 50,000 hours lifetime (L80B10)




5 years warranty

1 Uniform Chip



2 Exploded Diagram




3 UGR<19



# 2.Application

- OFFICE  
Meeting rooms, Open-plan offices, Offices, Sanitary areas
- SHOP & RETAIL  
Shopping mall, Supermarkets, Retail stores,
- EDUCATION  
Classrooms, Cafeteria, Chemical Lab, Pools
- ARCHITECTURAL  
Library, Concert hall,

### 3.Product Dimension



Model NO.	SizeA(mm)	Size B(mm)	Size C(mm)	Panel Cable Length(mm)	Driver Cable Length(mm)
P01CO-40XX-6262	620	620	10	200	150
P01CO-40XX-0606	595	595	10	200	150
P01CO-40XX-1203	1195	295	10	200	150
P01CO-54XX-1206	1195	595	10	200	150
P01CO-22XX-0603	595	295	10	200	150
P01CO-15XX-0303	295	295	10	200	150

### 4. Parameter

Model NO. / Length	Power (W)	Efficiency	
		100lm/W	120lm/W
P01CO-1206	54	5400	6480
P01CO-6262	40	4000	4800
P01CO-0606	40	4000	4800
P01CO-1203	40	4000	4800
P01CO-0603	22	1760	2640
P01CO-0303	15	1050	1800

**Notes:**



- above lumens based on 4000K Ra : 80
- All values in +25°C ambient temperature, luminous flux tolerance +-5%, output power tolerance +-5%.

Light Source : 4014/2835 SDCM<3 or 5  
 CRI Range : 80 / 90  
 CCT Range : WW(3000K) NW(4000K) DW(5000K) CW(6500K)  
 AC Input : 220-240V 50/60Hz  
 L70B10 @Ta 25 C : 69000h L70B50 @Ta 25 C : 78000h  
 Beam Angle : 120°  
 Light Efficiency : 100Lm/W, 120Lm/W  
 Size(mm) : 1206/1203/6262/0606/0603/0303  
 Recommended Installation Height : 2-6M  
 PF:≥0.93 THD<20% Power Efficiency:≥0.90  
 Temperature : (Storage : -40~+85°C) (Operating : -20~+40°C)

Dimmable Emergency Motion sensor


## 5. Standard Installation

### Install Map




#### 1 Built-in

- A: Push the panel into right size.
- B: Link the panel with steel cable.
- C: Install the fixture onto the ceiling and secure the fixture by steel cable.
- D: Adjust the position of the fixture and clean it.



#### 2 Suspending

- (PLS Note: Mounted box belongs to the optional accessories, pls place other order if you need.)
- A: Make a right position and screw hole
  - B: Screw the steel cable onto the ceiling
  - C: Hang the box under the steel cable and fix it with a steel cable.
  - D: Push the fixture into the mounted box and secure the Alu frame.
  - E: Adjust the position of the fixture and clean it.



#### 3 Ceiling Mounted

- (PLS Note: Mounted box belongs to the optional accessories, pls place other order if you need.)
- A: Make a right position and screw hole
  - B: Put the mounted box on the wall.
  - C: Push the fixture into the mounted box and secure the Alu frame.
  - D: Adjust the position of the fixture and clean it.


- Pls note : Above installation " A " belongs to our standard installation, if you want to choose our way of " B " and " C " installation then you need to select our optional accessories and pay.

Manual	steel cable	Metal Cover	
One package one pc	One package two pcs	One Lamp one pc	
	Metal Box	Metal hose	Mounted box
	One Lamp one pc	One Lamp one pc	One Lamp one pc

Standard accessories

Optional accessories

## 6.Packaging



### A.Packing list

Sequence Number	ModelNO.	Quantity
1	LED panel light	1pcs
2	Power supply	1pcs
3	Power supply box	1pcs
4	Manual	1pcs

Model No.	Singal Box	Pcs/CTN	N.W./Panel (kg)	G.W./CTN (kg)	Meas (cm)
P01CO-1206	1	2	6.9	17.28	124*66*10
P01CO-1203	1	5	3.16	28	125*34*23
P01CO-6262	1	5	3.42	22.18	68*68*23
P01CO-0606	1	5	3.1	20.04	65*65*23
P01CO-0603	1	5	1.617	10.58	65*35*23
P01CO-0303	1	10	0.835	22.5	67*34*23

- PLS Note : The current of the package's message pls check with the relative sales .

## 7. Attention

This specification is for reference only,we reserve the right to change without notice.If you need the updated info,please contact local distributors or visit our website at <http://www.ervan.cn>

This product is non-resistant to some chemical substances,please contact the manufacturer for the details.

ERVAN reserves the right of final explanation.