


# **INDOOR SPORTS LUMINAIRE--V10**

https://www.ervan.cn

V10 Indoor sports hall luminaire is designed according to the traditional tube fixture which is used widely, meanwhile meet the needs of all the professional requirement of the sports field such as low glare, comfortable light distribution, compatible with smart system, and most important is aprroved by ball impact testing.






1530mm

Mechanical Characteristics	
Certification	DIN18032-3 / CE / ROHS
Ingress protection rating(IP)	IP20
Impact resistance(IK)	IK10
Ambient temperature	-20~40°C
Protective class	Class I
_ Glow wire	650°C
Profile	Sheet metal
Cable entry	Entry on both ends
Terminal connector	3/5 push-in terminal connector
Housing color	White
Weight(Net)	11.5KG
Installation	Ceiling mounted   Suspension
Installation Height	4-20M

Electrical Characteristics	
Wiring	3/5x1.5mm <sup>2</sup> wires through; 3/5x2.5mm <sup>2</sup> wires through
Power	100W   150W   200W
Mains voltage	AC/DC 220~240V 50/60Hz
Power factor	≥0.9
THD	<20%
Flicker factor	<1%
SVM	< 0.4
Pst	<1
Function	DALI 1-10V Dimmable   Motion Sensor   Emergency
Circuit breakers	B10   B16   C10   C16
	100W 11 18 15 24
	150W 7 12 10 16
	200W 5 9 7 12
Linkable qty	INPUT   NX   NX   NX
	230vac 8(100W) 5(150W) 4(200W)

Photometrical Characteristics	
CCT	3000 / 4000 / 5000 / 6500K
CRI	80~95
Luminous flux	12500 / 18750 / 25000lm
Luminous efficacy	125lm/w
SDCM	3
Beam angle	90°
UGR	100W(19); 150W(20); 200W(22)
Service life	L80B10:100000h
Photobiological safety	RG0

## Optics



### Accessories

#### Material





### Description

Surface mounting Screws

Suspension Kits(2X0.5M chian+2x1M chain + brackets)